




Sturdy cast iron sliding table with linear guide and adjustment screws for easy, accurate set-up.



Advantages of tilting to the left:
Cleaner cut from above.
No collision with fence.
Workpiece cannot get jammed when cutting at the fence.

CE

JTS-250CS – CIRCULAR SAW

The JET SUPERSAW is a better saw.
With better specs. And a better price.


- ◆ Precision-ground, abrasionproof cast iron wings, just like the professional models
- ◆ Sawblade tilts to the left for safe operation at the fence and a lower risk of backlash for mitred cuts
- ◆ New Micro Glide fence with integrated micro adjustment and magnified cursor for greater precision and even more control comfort
- ◆ The JET SUPERSAW combines the features of an industrial saw with increased specification at excellent value for money
- ◆ Precision mitre gauge fence 0°/90°/135° adjustable. Adjustable fences
- ◆ A rugged steel cabinet guarantees stability for vibration free operation
- ◆ Durable powder coated finish (like all JET models) to make sure your JET SUPERSAW will look good for years

Standard equipment

- ◆ Table extension 435 x 500 mm
- ◆ Carbide tip saw blade 40-tooth
- ◆ Connecting tube incl. Y-fitting

Stock number 230V	708781KM
Stock number 400V	708781KT
Model	JTS-250CS
Cast iron table	705 x 685 mm
Blade diameter	250 mm
Bore diameter	30 mm
Max. depth of cut at 90°	82 mm
Tilting range of blade	90°–45° left
Width of cut	790 mm
Blade speed	4300 rpm
Dust port diameter	100 mm
Cast iron slide	355 x 685 mm
Sliding table max. width of cut in front of saw blade	725 mm
Motor: 230 V power output	1.75 HP / S: 100%
Motor: 230 V power input	3.1 HP / S: 40%
Motor: 400 V power output	3 HP / S: 100%
Motor: 400 V power input	5.7 HP / S: 40%
Weight	190 kg

Accessories



- ◆ 708118 Mobile base up to 250 kg
- ◆ 708119 Mobile base up to 500 kg



- ◆ 10000050 Circular saw blade Ø 250 40-tooth