

ORWAK 3410-SD

SLIDING DOOR

Orwak 3410-SD offers effective baling of large volumes of recyclable packaging and is the optimal choice for both cardboard and plastic. For easier and faster loading it is equipped with autostart and has a sliding door that opens automatically after each compaction cycle.



MORE PRODUCTIVE USE OF TIME

Less time spent on waste handling, more time devoted to your core activities.

VOLUME REDUCTION

More compaction = less waste volume to transport for recycling or disposal. Fewer transports required results in lower transportation costs and reduced CO₂ emissions.

MORE SPACE

Our baler rapidly minimizes the space the waste takes up, keeping aisles and passageways free and tidy.



ORWAK 3410-SD

Sliding door for easier and faster handling

SLIDING DOOR AND AUTOSTART

For even easier and faster loading the baler has a sliding door that opens automatically after each cycle. It is also equipped with an autostart function which allows the baler to start compacting the material as soon as the door closes.

EFFECTIVE COMPACTION

The long piston stroke gives highly compacted bales!

SAFE DOOR-OPENING

"The latch and wheel" locking system on the lower door allows the operator to gradually open the door in a controlled way even when compacting expanding materials.



ORWAK 3410-SD IS OPTIMIZED FOR:

PAPER

- + Cardboard
- + Shredded
- + Paper sacks

SPECIAL

- + Steel drums*
- Hazardous waste

PLASTIC FOIL

- + Shrink film
- + Plastic bags

* Optional insert is available for combined baler and drum crusher

HIGH CAPACITY

3410-SD has a generous loading aperture and offers high capacity. It is suitable for customers such as large industries and supermarkets with large amounts of packaging materials.

SILENT OPERATION CONTRIBUTES TO A BETTER WORKING ENVIRONMENT

Due to a silent type of hydraulics, the sound emission is low, which contributes to improving the working environment for the employees and is an important feature if the baler is installed close to customers.

SWITCH BETWEEN LP AND HP

Compacting cardboard or plastic foil? A switch conveniently located on the side of the machine makes it simple to alter the setting from High Pressure for cardboard to Low Pressure for plastic foil.


BALE INDICATOR

A bale indicator alerts you when the machine has reached its capacity.

DIMENSIONS AND SPECIFICATIONS

Dimensions					
A	B	C	D	E	F*
2962 mm	1613 mm	1151 mm	2400 mm	1106 mm	2150 mm

Energy consumption	
STANDBY MODE	MAXIMUM OPERATION ONE HOUR
2.7 W / H	626 W / H



WEIGHT (MACHINE) TOTAL: 1370 KG

*Transport Height

Technical specifications							
LOADING APERTURE	CYCLE TIME	PRESS FORCE	BALE SIZE	BALE WEIGHT	NOISE LEVEL	PROTECTION CLASS	OPERATING POWER
Width: 1113 mm Height: 550 mm	35 secs	24 ton, 240 kN	Width: 1200 mm Depth: 800 mm Height: 1000 mm	Cardboard: Up to 400 kg Plastic: Up to 450 kg	62.7 db (A)	IP 55	3-phase 3x400 V, 50 Hz



TOMRA Compaction AB

Box 58, SE-576 22 Sävsjö, Sweden
Tel: +46 382-157 00
Fax: +46 382-106 07
E-mail: info.compaction@tomra.com
www.tomracompaction.com

We reserve the right to make changes to specifications without prior notice.
Bale/bag/bin weights are dependent upon material type.